




Technical data and prices

Price group 4

Model		ML 262 DC	ML 352 DC	ML 522 DC
Cooling capacity	kW	2,6 (0,7-3,5)	3,5 (0,7-4,0)	5,2 (1,5-6,4)
Heating capacity	kW	3,1 (0,7-3,7)	4,2 (0,8-4,7)	5,9 (1,5-6,7)
Energy efficiency class cooling		A	A	A
Energy efficiency class heating		A	A	A
Yearly cooling/heating energy consumption 500 h	kWh	405/405	535/585	810/820
Operational area (size of room) approx.	m ³	80	110	160
Circulating air volume indoor unit max.	m ³ /h	350/420/500	370/450/550	600/700/800
Fan speeds		3	3	3
Operating range - indoor unit	°C	+16 to +31	+16 to +31	+16 to +31
Operating range - outdoor unit - cooling	°C	+5 to +50	+5 to +50	+5 to +50
Operating range - outdoor unit - heating	°C	-15 to +25	-15 to +25	-15 to +25
Sound pressure level per speed - indoor unit ¹⁾	dB (A)	29/34/39	31/37/40	37/39/42
Sound pressure level - outdoor unit ¹⁾	dB (A)	50	51	54
Power supply	V/Hz	230/1~/50	230/1~/50	230/1~/50
Cooling capacity / power consumption	kW/A	0,8/3,7	1,0/4,7	1,6/7,0
Heating capacity / power consumption	kW/A	0,8/3,8	1,1/5,2	1,6/7,2
Connection refrigerant pipes-liquid	Inches	¼	¼	¼
Connection refrigerant pipes-suction	Inches	⅜	½	½
Length of the refrigerant line length/height	m	20/8	20/8	25/10
Dimensions indoor unit H/W/D	mm	275/790/190	275/790/190	275/940/200
Dimensions outdoor unit H/W/D	mm	590/760/270	590/760/270	590/760/270
Weight - indoor unit / outdoor unit	kg	8,5/38,0	8,5/39,0	11,0/39,5
Compact units				
Price	€	729,-	795,-	1.260,-
Ref. no.		1632262	1632352	1632522

Accessories (see page 20)


¹⁾ At distance of 1 m in the open air



Single split system




Cooling and heating



Inverter technology



Infrared remote controller



Integrated filter-system



Automatic power failure restart